

# VarioClean Eco 150 ml and 500 ml

# Stihl Pty Ltd

BWES: **7918-44** Version No: **2.1** 

Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Issue Date: **08/11/2024** Print Date: **13/11/2024** L.GHS.AUS/NZ.EN.E

# SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### **Product Identifier**

Product name	VarioClean Eco 150 ml and 500 ml
Chemical Name	Not Applicable
Synonyms	Product code: 0782-516-8005; 0782-516-8006
Chemical formula	Not Applicable
Other means of identification	Not Available

# Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Cleaning agent. Use according to manufacturer's directions.
--------------------------	---

# Details of the manufacturer or supplier of the safety data sheet

Registered company name	Stihl Pty Ltd
Address	5 Kingston Park Court, Knoxfield VIC 3180 Australia
Telephone	+61 3 9215 666
Fax	Not Available
Website	Not Available
Email	csc@stihl.com.au

# Emergency telephone number

Association / Organisation	Poisons Information Centre Australia
Emergency telephone number(s)	131 126
Other emergency telephone number(s)	Not Available

# **SECTION 2 Hazards identification**

#### Classification of the substance or mixture

# HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

Poisons Schedule	Not Applicable
Classification <sup>[1]</sup>	Skin Corrosion/Irritation Category 2, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 1, Hazardous to the Aquatic Environment Long-Term Hazard Category 3
Legend:	1. Classified by BWES; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

# Label elements

Hazard pictogram(s)





Signal word

Dange

#### Hazard statement(s)

· · · · · · · · · · · · · · · · · · ·	
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H412	Harmful to aquatic life with long lasting effects.

Page 2 of 19

VarioClean Eco 150 ml and 500 ml

Issue Date: 08/11/2024 Print Date: 13/11/2024

Version No: 2.1

# Precautionary statement(s) Prevention

P280	Wear protective gloves, protective clothing, eye protection and face protection.
P261	Avoid breathing mist/vapours/spray.
P273	Avoid release to the environment.
P264	Wash all exposed external body areas thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.

# Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.
P302+P352	IF ON SKIN: Wash with plenty of water.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

#### Precautionary statement(s) Storage

Not Applicable

### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation. Not regulated for transport of Dangerous Goods.

Classification <sup>[1]</sup>	Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 2
Legend:	1. Classified by BWES; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by BWES using GHS/HSNO criteria	6.3A, 6.4A, 9.1B

#### Label elements

Hazard pictogram(s)





Signal word

Warning

### Hazard statement(s)

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

# Precautionary statement(s) Prevention

•	` '	
	P273	Avoid release to the environment.
	P280	Wear protective gloves, protective clothing, eye protection and face protection.
	P264	Wash all exposed external body areas thoroughly after handling.

# Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P391	Collect spillage.
P302+P352	IF ON SKIN: Wash with plenty of water.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

# Precautionary statement(s) Storage

Not Applicable

## Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

# **SECTION 3 Composition / information on ingredients**

# Substances

See section below for composition of Mixtures

Page 3 of 19

VarioClean Eco 150 ml and 500 ml

Issue Date: 08/11/2024 Print Date: 13/11/2024

#### **Mixtures**

Part Number:

Version No: 2.1

CAS No	%[weight]	Name	
56-81-5	5-<10	gl <u>vcerol</u>	
68515-73-1	3-<5	<u>decyl-D-glucopyranoside</u>	
61789-40-0	1-<3	cocamidopropylbetaine	
110615-47-9	<1 (C10-16)alkyl D-glycopyranoside		
Not Available	balance Ingredients determined not to be hazardous		
Legend:	1. Classified by BWES; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available		

# **SECTION 4 First aid measures**

Description of first aid measures				
	If this product comes in contact with the eyes:			
	▶ Immediately hold eyelids apart and flush the eye continuously with running water.			
Eye Contact	• Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.			
	Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.			
	▶ Transport to hospital or doctor without delay.			
	▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.			
	If skin contact occurs:			
Skin Contact	▶ Immediately remove all contaminated clothing, including footwear.			
	<ul> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>			
	▶ If fumes or combustion products are inhaled remove from contaminated area.			
	Lay patient down. Keep warm and rested.			
Inhalation	<ul> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> </ul>			
	<ul> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor, without delay.</li> </ul>			
	► If swallowed do <b>NOT</b> induce vomiting.			
Ingestion	<ul> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> </ul>			
	Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.			
	Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.			

# Indication of any immediate medical attention and special treatment needed

Seek medical advice.

Treat symptomatically.

# **SECTION 5 Firefighting measures**

# Extinguishing media

- Water spray or fog.

- Foam.
  Dry chemical powder.
  BCF (where regulations permit).
- Carbon dioxide.

# Special hazards arising from the substrate or mixture

Fire Incompatibility  Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may		
dvice for firefighters		
	▶ Alert Fire Brigade and tell them location and nature of hazard.	
	▶ Wear full body protective clothing with breathing apparatus.	
Fire Fighting Prevent, by any means available, spillage from entering drains or water course.		
	Use water delivered as a fine spray to control fire and cool adjacent area.	
	Avoid spraying water onto liquid pools.	
	▶ DO NOT approach containers suspected to be hot.	
	Cool fire exposed containers with water spray from a protected location.	
	▶ If safe to do so, remove containers from path of fire.	

Page 4 of 19 Chemwatch: 7918-44

VarioClean Eco 150 ml and 500 ml

Issue Date: 08/11/2024 Print Date: 13/11/2024

# Fire/Explosion Hazard

- Combustible.
- ▶ Slight fire hazard when exposed to heat or flame.
- ▶ Heating may cause expansion or decomposition leading to violent rupture of containers.
- ▶ On combustion, may emit toxic fumes of carbon monoxide (CO).
- May emit acrid smoke.
- ▶ Mists containing combustible materials may be explosive.

Combustion products include:

carbon dioxide (CO2) nitrogen oxides (NOx)

other pyrolysis products typical of burning organic material.

May emit poisonous fumes. May emit corrosive fumes.

#### **SECTION 6 Accidental release measures**

# Personal precautions, protective equipment and emergency procedures

See section 8

Version No: 2.1

Page **5** of **19** Chemwatch: 7918-44 Issue Date: 08/11/2024 Print Date: 13/11/2024 VarioClean Eco 150 ml and 500 ml Version No: 2.1

#### **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

methods and material for containment and cleaning up			
Minor Spills	<ul> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Contain and absorb spill with sand, earth, inert material or vermiculite.</li> <li>Wipe up.</li> <li>Place in a suitable, labelled container for waste disposal.</li> </ul>		
Major Spills	Moderate hazard.  Clear area of personnel and move upwind.  Alert Fire Brigade and tell them location and nature of hazard.  Wear breathing apparatus plus protective gloves.  Prevent, by any means available, spillage from entering drains or water course.  No smoking, naked lights or ignition sources.  Increase ventilation.  Stop leak if safe to do so.  Contain spill with sand, earth or vermiculite.  Collect recoverable product into labelled containers for recycling.  Absorb remaining product with sand, earth or vermiculite.  Collect solid residues and seal in labelled drums for disposal.  Wash area and prevent runoff into drains.  If contamination of drains or waterways occurs, advise emergency services.		

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

Precautions for safe handling				
	DO NOT allow clothing wet with material to stay in contact with skin     Avoid all personal contact, including inhalation.			
	<ul> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> </ul>			
Safe handling	<ul> <li>DO NOT enter confined spaces until atmosphere has been checked.</li> <li>Avoid smoking, naked lights or ignition sources.</li> <li>Avoid contact with incompatible materials.</li> </ul>			
	► When handling, DO NOT eat, drink or smoke.			
	<ul> <li>Keep containers securely sealed when not in use.</li> <li>Avoid physical damage to containers.</li> </ul>			
	<ul> <li>Always wash hands with soap and water after handling.</li> <li>Work clothes should be laundered separately.</li> <li>Use good occupational work practice.</li> </ul>			
	Observe manufacturer's storage and handling recommendations contained within this SDS.			
	Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.			
	Store in original containers.      Keep containers securely sealed.			
Other information				
	No smoking, naked lights or ignition sources.			
	<ul> <li>Store in a cool, dry, well-ventilated area.</li> <li>Store away from incompatible materials and foodstuff containers.</li> </ul>			
	▶ Protect containers against physical damage and check regularly for leaks.			
	Observe manufacturer's storage and handling recommendations contained within this SDS.			

# Conditions for safe storage, including any incompatibilities

Suitable container	container Metal can or drum	
	▶ Packaging as recommended by manufacturer.	
	Check all containers are clearly labelled and free from leaks.	
Storage incompatibility	Avoid reaction with oxidising agents	

# SECTION 8 Exposure controls / personal protection

# **Control parameters**

Occupational Exposure Limits (OEL)

Continued...

Material Ingredient

Version No: 2.1

Page 6 of 19

VarioClean Eco 150 ml and 500 ml

Issue Date: **08/11/2024**Print Date: **13/11/2024** 

INGREDIENT DATA

Ingredient	Original IDLH	Revised IDLH
glycerol	Not Available	Not Available
decyl-D-glucopyranoside	Not Available	Not Available
cocamidopropylbetaine	Not Available	Not Available
(C10-16)alkyl D- glycopyranoside	Not Available	Not Available

Occupational Exposure Banding

decyl-D-glucopyranoside cocamidopropylbetaine (C10-16)alkyl D-

Page 7 of 19

Part Number: VarioClean Eco 150 ml and 500 ml

Е

Issue Date: **08/11/2024**Print Date: **13/11/2024** 

Occupational Exposure Band Rating	Occupational Exposure Band Limit
D	> 0.01 to ≤ 0.1 mg/m³
Е	≤ 0.1 ppm

Notes:

Version No: 2.1

Ingredient

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

≤ 0.1 ppm

#### MATERIAL DATA

glycopyranoside

#### **Exposure controls**

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in special circumstances. If risk of overexposure exists, wear approved respirator. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. Provide adequate ventilation in warehouses and enclosed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

# Appropriate engineering controls

Type of Contaminant: Air Speed: 0.25-0.5 m/s (50solvent, vapours, degreasing etc., evaporating from tank (in still air). 100 f/min) aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, 0.5-1 m/s (100-200 f/min.) spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active 1-2.5 m/s (200generation into zone of rapid air motion) 500 f/min.) grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone 2.5-10 m/s (500of very high rapid air motion) 2000 f/min.)

Within each range the appropriate value depends on:

Lower end of the range	Upper end of the range
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity
3: Intermittent, low production.	3: High production, heavy use
4: Large hood or large air mass in motion	4: Small hood-local control only

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

#### Individual protection measures, such as personal protective equipment









# Eye and face protection

- ▶ Safety glasses with side shields.
- ► Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
  - Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

#### Skin protection

See Hand protection below

VarioClean Eco 150 ml and 500 ml

#### Page 8 of 19 Issue Date: 08/11/2024 Print Date: 13/11/2024

#### Hands/feet protection

Version No: 2.1

- ▶ Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber

#### NOTE:

- ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.
- Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:

- · frequency and duration of contact,
- chemical resistance of glove material,
- · glove thickness and
- dexterity

VarioClean Eco 150 ml and 500 ml

Page 9 of 19 Issue Date: 08/11/2024 Print Date: 13/11/2024

Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).

- When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- · When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.
- Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.
- Contaminated gloves should be replaced.

As defined in ASTM F-739-96 in any application, gloves are rated as:

- · Excellent when breakthrough time > 480 min
- · Good when breakthrough time > 20 min
- · Fair when breakthrough time < 20 min
- · Poor when glove material degrades

For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.

It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.

Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task

- Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example: · Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are
- only likely to give short duration protection and would normally be just for single use applications, then disposed of. · Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion

or puncture potential Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

#### **Body protection**

See Other protection below

# Other protection

- Overalls.
- ▶ P.V.C apron.
- Barrier cream.
- Skin cleansing cream.
- ▶ Eye wash unit.

#### Recommended material(s)

Version No: 2.1

### **GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:

#### "Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computergenerated selection:

VarioClean Eco 150 ml and 500 ml

Material	СРІ
NATURAL RUBBER	Α
NATURAL+NEOPRENE	Α
NITRILE	Α

CPI - BWES Performance Index A:

Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

#### Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AK-AUS P2	-	AK-PAPR-AUS / Class 1 P2
up to 50 x ES	-	AK-AUS / Class 1 P2	-
up to 100 x ES	-	AK-2 P2	AK-PAPR-2 P2 ^

# ^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

  • Cartridge performance is affected by humidity. Cartridges should be changed after
- 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

# SECTION 9 Physical and chemical properties

#### Information on basic physical and chemical properties

Appearance	Colourless liquid with fruit like odour; mixes with water.		
Physical state	Liquid Relative density (Water = 1) 1.07-1.08		
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	11-11.2	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	<20.5

Pi boiling point and boiling range (°C) Not Available VarioClean Eco 15 Not Applicable Print Date: 13/11/2024

Version No: 2.1

Part Number: Version No: **2.1** 

# Page 11 of 19 VarioClean Eco 150 ml and 500 ml

Issue Date: 08/11/2024 Print Date: 13/11/2024

Flash point (°C)	Not Available	Taste	Not Available
Flash point (*C)	Not Available	raste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

# **SECTION 10 Stability and reactivity**

Reactivity	See section 7	
Chemical stability  • Unstable in the presence of incompatible materials. • Product is considered stable. • Hazardous polymerisation will not occur.		
Possibility of hazardous reactions	See section 7	
Conditions to avoid	See section 7	
Incompatible materials	See section 7	
Hazardous decomposition products	See section 5	

# **SECTION 11 Toxicological information**

Information on toxicological eff	fects
Inhaled	Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.
Ingestion	Accidental ingestion of the material may be damaging to the health of the individual.
Skin Contact	Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.  The material may accentuate any pre-existing dermatitis condition Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.  One of the mechanisms of skin irritation caused by surfactants is considered to be denaturation of the proteins of skin. It has also been established that there is a connection between the potential of surfactants to denature protein in vitro and their effect on the skin. Nonionic surfactants do not carry any net charge and, therefore, they can only form hydrophobic bonds with proteins. For this reason, proteins are not deactivated by nonionic surfactants, and proteins with poor solubility are not solubilized by nonionic surfactants  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
Eye	When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation.
Chronic	Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals.  Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological, irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even to tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitiser will become hyper-responsive and it is impossible to identify in advance who are likely to become hyper-responsive.  Substances than can cuase occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing air-way hyper-responsiveness. The latter substances are not classified as asthmagens or respiratory sensitisers.  Wherever it is reasonably practicable, exposure to substances that can cuase occupational asthma should be prevented. Where this is not

Wherever it is reasonably practicable, exposure to substances that can cuase occupational asthma should be prevented. Where this is not possible the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance. Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or

Prolonged or repeated skin contact may cause degreasing with drying, cracking and dermatitis following.

biochemical systems.

VarioClean Eco 150 ml and 500 ml	TOXICITY  Not Available	IRRITATION  Not Available
glycerol	TOXICITY	IRRITATION
	Dermal (Guinea Pig) LD50: 58500 mg/kg <sup>[1]</sup>	Eye (Rodent - rabbit): 500mg/24H - Mild

Page 12 of 19

VarioClean Eco 150 ml and 500 ml

Part Number: Version No: **2.1**  Issue Date: **08/11/2024**Print Date: **13/11/2024** 

	Inhalation (Rat) LC50: >5.85 mg/L4h <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Oral (Mouse) LD50; 4090 mg/kg <sup>[2]</sup>	Skin (Rodent - rabbit): 500mg/24H - Mild
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
	TOXICITY	IRRITATION
decyl-D-glucopyranoside	Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup>	Not Available
	Oral (Rat) LD50: >2000 mg/kg <sup>[1]</sup>	
	TOXICITY	IRRITATION
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye (Rodent - rabbit): 100uL/24H - Severe
	Oral (Rat) LD50: 2700 mg/kg <sup>[2]</sup>	Eye: adverse effect observed (irreversible damage) <sup>[1]</sup>
cocamidopropylbetaine		Eye: adverse effect observed (irritating) <sup>[1]</sup>
		Skin: adverse effect observed (irritating) <sup>[1]</sup>
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
	TOXICITY	IRRITATION
(C10-16)alkyl D- glycopyranoside	Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup>	Skin (Rodent - rabbit): 30 - Mild
	Oral (Rat) LD50: >2000 mg/kg <sup>[1]</sup>	

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.

Acute toxicity: Glycerol is of a low order of acute oral and dermal toxicity with LD50 values in excess of 4000 mg/kg bw. At very high dose levels, the signs of toxicity include tremor and hyperaemia of the gastro-intestinal -tract. Skin and eye irritation studies indicate that glycerol has low potential to irritate the skin and the eye. The available human and animal data, together with the very widespread potential for exposure and the absence of case reports of sensitisation, indicate that glycerol is not a skin sensitiser.

# GLYCEROL

Repeat dose toxicity: Repeated oral exposure to glycerol does not induce adverse effects other than local irritation of the gastro-intestinal tract. The overall NOEL after prolonged treatment with glycerol is 10,000 mg/kg bw/day (20% in diet). At this dose level no systemic or local effects were observed. For inhalation exposure to aerosols, the NOAEC for local irritant effects to the upper respiratory tract is 165 mg/m3 and 662 mg/m3 for systemic effects.

**Genotoxicity:** Glycerol is free from structural alerts, which raise concern for mutagenicity. Glycerol does not induce gene mutations in bacterial strains, chromosomal effects in mammalian cells or primary DNA damage *in vitro*. Results of a limited gene mutation test in mammalian cells were of uncertain biological relevance. *In vivo*, glycerol produced no statistically significant effect in a chromosome aberrations and dominant lethal study. However, the limited details provided and the absence of a positive control, prevent any reliable conclusions to be drawn from the *in vivo* data. Overall, glycerol is not considered to possess genotoxic potential.

Carcinogenicity: The experimental data from a limited 2 year dietary study in the rat does not provide any basis for concerns in relation to carcinogenicity. Data from non-guideline studies designed to investigate tumour promotion activity in male mice suggest that oral administration of glycerol up to 20 weeks had a weak promotion effect on the incidence of tumour formation.

Reproductive and developmental toxicity: No effects on fertility and reproductive performance were observed in a two generation study with glycerol administered by gavage (NOAEL 2000 mg/kg bw/day). No maternal toxicity or teratogenic effects were seen in the rat, mouse or rabbit at the highest dose levels tested in a guideline comparable teratogenicity study (NOEL 1180 mg/kg bw/day).

### DECYL-D-GLUCOPYRANOSIDE

No significant acute toxicological data identified in literature search.

#### COCAMIDOPROPYLBETAINE

\* [Van Waters and Rogers] \*\* [Canada Colors and Chemicals Ltd.] Toxicokinetics, metabolism and distribution. Absorption of the chemical across dermal and gastrointestinal membranes is possible based on the relatively low molecular weight of the chemical (500 Da) and given that it is a surfactant (EC, 2003). Acute toxicity. Acute oral toxicity studies in rats and mice indicated that the LD50 values of the chemical (at 30-35.61% concentration) ranged from 1800 mg/kg bw (male rats) up to 5000 mg/kg bw, with mortalities noted in most studies (CIR, 2010). Of note is an acute oral toxicity study conducted in Sprague-Dawley rats (5/sex) at a single dose of 1800 mg/kg bw (formulation containing 35.61% of the chemical), where no males but all five females died. Overall, the data suggests that mortality occurs following oral administration of the chemical and that it may be an acute oral toxicant. Therefore, based on these data the chemical may be harmful if swallowed. An acute dermal toxicity study in rats was conducted using 2000 mg/kg bw of a 31% formulation of the chemical (CIR, 2010). Irritation was observed, but there were no clinical signs of systemic toxicity or mortalities. The lack of effects in this study suggests that the chemical is likely to be of low acute dermal toxicity. Irritation. The chemical has a quaternary ammonium functional group, which is a structural alert for corrosion Numerous skin irritation studies, conducted with formulations containing 7.5-30% of the chemical, indicated that the chemical has irritant properties. The studies were, in-general, conducted under occlusive conditions, with exposure times of up to 24 hours (7.5-10%). Based on the information available, the chemical is likely to be a skin irritant. Eye irritation studies with the chemical showed that corrosive and necrotic effects occurred at 30% whereas less severe effects were observed at lower concentrations of 2.3-10% The chemical is classified with the risk phrase R36: Irritating to eyes, however, based on studies conducted on the chemical it may be a severe eye irritant. Sensitisation. The chemical has a quaternary ammonium functional group, which is a structural alert for sensitisation ( Conflicting results have been obtained with the chemical in animal studies. Positive results were reported in an LLNA study (an EC3 value was not reported). In addition, positive results were obtained in two guinea pig maximisation studies conducted by a single laboratory, the first at 3% induction and 3% challenge, and the second at 0.15% induction and 0.015% challenge. However, there was no sensitisation in a guinea pig maximisation test when the chemical was tested at 6% induction and 1% challenge. In addition, no sensitisation was observed in another test in guinea pigs at 0.75% induction and 0.02% challenge. No evidence of sensitisation was reported in a HRIPT on a formulation containing the chemical at 0.6% concentration (a 10% dilution of a ~6% formulation) with 110 volunteers. In HRIPT studies on formulations containing the chemical, no evidence of sensitisation was reported at concentrations of 1.87% (88 subjects), 0.93% (93 subjects), 0.3% (100 subjects), 1.5-3.0% (141 subjects), 6.0% (210 subjects), 0.018% (27 subjects). However, positive results were observed in provocative studies conducted on formulations containing the chemical (at 0.3-1% concentration), conducted in subjects diagnosed with various forms of contact dermatitis, suggesting that the chemical may cause reactions in sensitive individuals In one study authors note that sensitisation effects of the chemical (and related compounds) are most likely due to the impurities, including DMAPA and amidopropyl dimethylamines,

Version No: 2.1

Page 13 of 19

#### VarioClean Eco 150 ml and 500 ml

Issue Date: 08/11/2024 Print Date: 13/11/2024

however, they do not exclude the possibility of the causing the sensitisation. The potential for skin sensitisation, due to the presence of the above impurities in the chemical, will be limited by their reported low concentration In summary, a definitive conclusion cannot be made on the skin sensitisation potential of the chemical. The available information suggests that skin sensitisation is possible. Although there are some inconsistencies in the results reported for studies conducted on the chemical, the scientific data points towards the positive findings being caused by impurities, in particular DMAPA and amidopropyl dimethylamines, which are present in the chemical at low concentrations. Repeated Dose Toxicity. In a 28-day repeated dose oral toxicity study, rats were administered a 30.6% solution of the chemical at 0, 100, 500 or 1000 mg/kg bw/day. Inflammation of the non-glandular stomach was noted in animals of the high-dose group, although this effect was attributed to the irritant properties of the test material. Mortality was also observed in this study at all treatment levels but there was no do response relationship. In another 28-day repeated dose oral toxicity study, rats were administered a solution containing the chemical (concentration not stated) at 0, 250, 500 or 1000 mg/kg bw/day. The NOEL was reported as 500 mg/kg bw/day, which appears to be based on non-systemic irritant effects on the non-glandular stomach. No mortalities were observed In a 90-day repeated dose oral toxicity study, rats were administered a solution containing the chemical (concentration not stated) at 0, 250, 500 or 1000 mg/kg bw/day. There were no mortalities and the noted effects are isolated to the stomach region and appear to be irritant in nature. The NOEL established by the study authors was 250 mg/kg bw/day, based on these effects. Mutagenicity. The chemical was not mutagenic in numerous bacterial reverse mutation assays. Negative results were also obtained for the chemical in a mouse lymphoma test and a micronucleus test in mice Carcinogenicity. No signs of carcinogenicity were noted in a 20 month dermal study in mice (3 applications/week) for a hair dye formulation containing the chemical at a concentration of 0.09% The formation of nitrosamines is possible. Secondary amides (and the identified impurities) may serve as substrates for N-nitrosation, therefore formulation with N-nitrosating agents should be avoided Possible cross-reactions to several fatty acid amidopropyl dimethylamines were observed in patients that were reported to have allergic contact dermatitis to a baby lotion that contained 0.3% oleamidopropyl dimethylamine.

Stearamidopropyl dimethylamine at 2% in hair conditioners was not a contact sensitiser when tested neat or diluted to 30%. However, irritation reactions were observed.

A 10-year retrospective study found that out of 46 patients with confirmed allergic eyelid dermatitis, 10.9% had relevant reactions to oleamidopropyl dimethylamine and 4.3% had relevant reactions to cocamidopropyl dimethylamine

Several cases of allergic contact dermatitis were reported in patients from the Netherlands that had used a particular type of body lotion that contained oleamidopropyl dimethylamine.

In 12 patients tested with their personal cosmetics, containing the fatty acid amidopropyl dimethylamine cocamidopropyl betaine (CAPB), 9 had positive reactions to at least one dilution and 5 had irritant reactions. All except 3 patients, who were not tested, had 2 or 3+ reaction to the 3,3-dimethylaminopropylamine (DMAPA, the reactant used in producing fatty acid amidopropyl dimethylamines) at concentrations as low as 0.05%. The presence of DMAPA was investigated via thin-layer chromatography in the personal cosmetics of 4 of the patients that had positive reactions. DMAPA was measured in the products at 50 - 150 ppm suggesting that the sensitising agent in CAPB-induced allergy is DMAPA.

The sensitisation potential of a 4% aqueous liquid fabric softener formulation containing 0.5% stearyl/palmitylamidopropyl dimethylamine was investigated using. The test material caused some irritation in most volunteers. After a rest period of 2 weeks, the subjects received challenge patches with the same concentration of test material on both arms. Patch sites were graded 48 and 96 h after patching. Eight subjects reacted at challenge, and 7 of the eight submitted to rechallenge with 4% and 0.4% aqueous formulations. No reactions indicative of sensitisation occurred at rechallenge. The test formulation containing stearyl/palmitylamidopropyl dimethylamine had no significant sensitisation potential.subjects.

Most undiluted cationic surfactants satisfy the criteria for classification as Harmful (Xn) with R22 and as Irritant (Xi) for skin and eyes with R38 and R41

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis. For betaines:

Several sources revealing data on skin irritation, skin sensitisation and dermal absorption in humans are available for CAS 683-10-3, the C12-alkyldimethyl betaine, which is the most frequently occurring betaine because it is one of the components of most of the substances of the alkyldimethyl betaine group, among those also Betaines, C12-14 (even numbered)-alkyldimethyl. Therefore, read-across of exposurerelated observations in humans from CAS 683-10-3 is justified. Data from several human closed patch tests demonstrate skin irritation in humans ranging from mild to strong under occlusive conditions even with concentrations as low as 1%. In contrast, exposure to 0.1% under open conditions did not induce any positive skin reactions.

Information on skin sensitisation in humans is available from a closed human patch test with CAS 683-10-3. After an induction period of 6 days with 0.1% of active ingredient, followed by a treatment-free period of 10 days, the volunteers were challenged under occlusive conditions for 24 hours. No reactions were observed immediately after challenge; during the next 4 days only irritation reactions were observed.

This finding was further supported by industrial medical monitoring data. Workers involved in the production of CAS 683-10-3 are routinely checked every 3 years for signs of skin sensitisation, respiratory irritation, skin irritation and eye irritation. During these examinations no signs of the aforementioned disorders were observed which were related to the test substance

Moreover, a study focusing on dermal uptake of C12-alkyldimethyl betaine) into human skin and the effects of surfactants on skin barrier function demonstrated that only up to 0.4% of the applied dose was absorbed within 30 minutes of exposure, with absorbance being dependent on the concentration applied. Tape stripping of the skin revealed that the administered test substance was primarily located in the outer stratum corneum layer

Test material does not demonstrate mutagenic or clastogenic effects in bacteria or mammalian cells in vitro

Amphoteric surfactants are easily absorbed in the intestine and are excreted partly unchanged via the faeces. Metabolisation to CO2 and short-chained fatty acids also occur. No tendency to accumulation in the organism or storage of betaines in certain organs has been detected. Betaines generally have a low acute toxicity. E.g., LD50 values for cocoamidopropylbetaine (30% solution) by oral administration have been determined to 4.910 mg/kg body weight in rats.

Betaines do not carry any net charge, and, therefore, they can only form hydrophobic bonds with proteins in the skin. This may be the explanation for the low protein denaturation potential of betaines as the ion-binding of other surfactants contributes to denaturation. In combination with anionic surfactants a positive synergistic effect with regard to skin compatibility is often found. Compared to a 20% solution of C12 alkyl sulfate (AS; sodium lauryl sulfate) alone, decreased erythema was observed for the combination of 20% C12 AS and 10% cocoamidopropyl betaine one hour after the removal of patches. The combination of cocoamidopropyl betaine and C12 AS also reduced swelling of the skin, and generally interactions between amphoterics and AS produce less swelling and result in milder skin reactions. Concentrated betaines are expected to be irritant to skin and eyes. Diluted solutions (3-10%) are not irritant to skin, but they are mildly irritant to the eyes (4.5%)

No evidence of delayed contact hypersensitivity was found in guinea pigs after topically administrated solutions of 10% cocoa midopropyl betaine by using the Magnusson-Kligman maximization test. Various instances of contact allergy to cocoamidopropyl betaine have been reported. In all of the reports it was concluded that the observed skin reactions were due to the presence of 3-dimethylaminopropylamine which is an impurity in cocoamidopropyl betaine. This impurity is an intermediate in the synthesis of alkylamidopropyldimethylamines that are intermediates in the synthesis of the corresponding alkylamido betaines.

Cocoamidopropyl betaine was proven to be non-mutagenic to Salmonella typhimurium in the Ames Salmonella/microsome reverse mutation assay. Short-term genotoxicity tests have shown negative results of mutagenicity for lauryl betaine in various strains of Salmonella typhimurium.

(C10-16)ALKYL D-GLYCOPYRANOSIDE

Acute inhalation hazard (rat) - no mortalities after 7 hour exposure in a highly enriched and/ or saturated atmosphere at 200 deg. C\* \*Redox MSDS (LD50 calculated)

DECYL-D-**GLUCOPYRANOSIDE &** COCAMIDOPROPYLBETAINE & (C10-16)ALKYL D-GLYCOPYRANOSIDE The following information refers to contact allergens as a group and may not be specific to this product.

Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into

Version No: 2.1

# Page 14 of 19 VarioClean Eco 150 ml and 500 ml

Issue Date: **08/11/2024**Print Date: **13/11/2024** 

contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.

Alkyl glycosides (syn: alkyl polyglucosides, alkyl polyglycosides, APGs) are considered non-irritating to skin, but irritating to eyes at very high concentrations. A general classification of a 65% C8 alkyl glycoside solution according to the Substance Directive 67/548/EEC is Irritating (Xi) with the risk phrase R41 (Risk of serious damage to the eyes) or R36 (Irritating to the eyes) (Akzo Nobel 1998).

#### Acute toxicity:

In single dose dermal studies with caprylyl/capryl glucoside and C10-16 alkyl glucoside (both 50% a.i., n:1.6) in rabbits, the LD50 was greater than the 2000 mg/kg dose administered. In oral studies with the same test substances, none of the mice dosed with 2000 mg/kg caprylyl glucoside and none of the rats dosed with 5000 mg/kg C10-16 alkyl glucoside died during the study.

#### Ocular:

In system studies for ocular irritation, the ocular irritation potential of decyl, lauryl, C10-16 alkyl, and coco-glucosides was non to slightly irritating and of caprylyl/ capryl glucoside was highly irritating. In a HET-CAM study with APG of varying proportions of alkyl chain length, the ocular irritation potential increased with the increased proportion of shorter-chain APGs. In studies using rabbits, neutralized lauryl glucoside produced slight ocular reactions. Caprylyl/ capryl glucoside was severely irritating to rabbit eyes when tested undiluted; the irritation threshold value was 10% for 30% a.i.caprylyl/capryl glucoside and 5% for 60% a.i. caprylyl/capryl glucoside.

#### Dermal:

In an in vitro dermal absorption study using human skin samples, the mean absorbed dose of 10% caprylyl/ capryl glucoside was 0.01%. APGs of varying chain length (C8/10 to C12/16; 15-70% a.i.) are potentially irritating with irritation potential decreasing with increasing chain length, and, independent of the degree of polymerisation, the irritation was concentration-dependent. The primary dermal irritation indices (PDIIs) ranged from 0.0 to 4.6 in rabbits. (A PDII of 2 was considered a positive responder).

In clinical studies, the dermal irritation of decyl, lauryl, and coco-glucosides was evaluated in epicutaneous patch (2.0% a.i.) and soap chamber tests (1.0% a.i.), and decyl glucoside was evaluated in a single insult occlusive patch test SIOPT (0.5% a.i.). At most, these ingredients were slightly irritating

#### Ingestion

DECYL-D-

16)ALKYL D-

GLYCOPYRANOSIDE

**GLUCOPYRANOSIDE & (C10-**

In an oral study in which female mice were dosed by gavage with a 5% aq. solution of caprylyl [U-14C]glucoside, the highest levels of radioactivity at 2 h after dosing were found in the stomach, intestines, liver, and kidney. The radioactivity in the stomach was primarily unchanged substrate, while only a trace amount found in the liver was unchanged. Labeled glucose was found in all of these organs. In a feeding study in rats in which dietary sucrose was replaced with 10 or 20% ethyl glucoside for 39 days, 60-90% of the ingested ethyl glucoside was recovered in the urine.

Repeat dose toxicity:

In 2-wk repeated dose dermal studies in rabbits with 60% active caprylyl/capryl glucoside, occlusive applications produced testicular effects, while non-occlusive application did not. In the two occlusive studies, one with 0.09 and 1.8 g a.i./kg and the other with 0.14-1.25 g a.i./kg, an NOEL for testicular effects could not be established. In the non-occlusive study, the NOEL for systemic toxicity was 0.18 g a.i./kg caprylyl/capryl glucoside. Severe dermal irritation was observed in both occlusive studies, while slight to moderate irritation was reported in the non-

Dermal application of 60% active caprylyl/capryl glucoside, 0.9-1.8 g a.i./kg, under occlusive conditions may affect the testes and accessory sex glands of rabbits; however, it was not clear if the effects were test-article related or due to stress

of the occlusive procedure and resulting irritation and weight loss. Lauryl glucoside, 100-1000 mg/kg by gavage, did not produce adverse reproductive or developmental effects. Lauryl glucoside, 0.1-10,000 nmol, did not have any effects in in vitro oestrogenicity assays

In oral repeated dose toxicity studies, moderately-dilated renal tubules were observed in 3 of 6 rats fed 20% ethyl glucoside for 39 days, but in none of the rats fed 10% ethyl glucoside. Kidney weights were statistically significantly increased in the test animals. In rats dosed orally with 250-1000 mg/kg C12/16 APG for 13 wks, reversible irritation and ulceration of the stomach mucosa was observed, but there was no systemic toxicity reported for any group.

# Mutagenicity:

Alkyl polyglucoses (polyglycoses; APGs) (chain length not specified), tested at 8-500 ug/l and 11-900 ug/plate in distilled water, were not mutagenic in Ames tests with or without metabolic activation. C10-16 APG, tested at concentrations of <= 160 ug/ml with and without metabolic activation, was not clastogenic.

#### Sensitisation:

Glucosides with alkyl chain lengths ranging from C8-C10 to >C18, as well as a C18 branched glucoside, were evaluated in both the guinea pig maximisation test (GPMT), at concentrations of 1.25-10% for intradermal induction, 5-100% for epidermal induction, and 2.5-50% for challenge, and the local lymph node assay (LLNA) at concentrations of 1.25-50%. None of the glucosides tested were irritants or sensitisers in the GPMT, but the LLNA indicated that one C12-C18 glucoside, C14 glucoside, and C18 branched glucoside may cause skin sensitization at concentrations of 8.4%, 5.9%, and 0.43%, respectively. The sensitization potential of C12/16 APG was evaluated in studies in guinea pigs using the Buebler

method (test concentrations of 20%) and the Magnusson-Kligman protocol (1, 60, and 10% used for intracutaneous induction, epidermal induction, and epidermal challenge respectively). C12/16 APG was not a sensitiser in the Buehler or

Magnusson-Kligman studies. In clinical testing, the sensitization potential of 0.5, 0.75, and 1.8% a.i. decyl glucoside (in formulation), 5% a.i. aq. decyl and lauryl glucoside, and 1% a.i. aq. coco-glucoside was evaluated in Human Repeat Insult Patch Tests (HRIPTs). These ingredients were not irritating or sensitising.

CIR Expert Panel Meeting, September 2011

Acute Toxicity	X	Carcinogenicity	×
Skin Irritation/Corrosion	~	Reproductivity	×
Serious Eye Damage/Irritation	×	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

💢 – Data either not available or does not fill the criteria for classification

Data available to make classification

# **SECTION 12 Ecological information**

#### Toxicity

V	Endpoint	Test Duration (hr)	Species	Value Sor
VarioClean Eco 150 ml and 500 ml	Not Available	Not Available	Not Available	Not Not Available Ava
	Endpoint	Test Duration (hr)	Species	Value Se
glycerol	EC0(ECx)	24h	Crustacea	>500mg/l 1
	LC50	96h	Fish	>11mg/L 2
decyl-D-glucopyranoside	Endpoint	Test Duration (hr)	Species	Value S

Version No: 2.1

Page 15 of 19

VarioClean Eco 150 ml and 500 ml

Issue Date: **08/11/2024**Print Date: **13/11/2024** 

	EC50	72h	Algae or other aquatic plants	12.43mg/l	2
	NOEC(ECx)	672h	Fish	1mg/l	2
	LC50	96h	Fish	96.64mg/l	2
	EC50	48h	Crustacea	31.62mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	96h	Algae or other aquatic plants	0.55mg/l	1
cocamidopropylbetaine	EC50	72h	Algae or other aquatic plants	1- 10mg/l	1
	EC0(ECx)	96h	Algae or other aquatic plants	0.09mg/l	1
	LC50	96h	Fish	1mg/l	1
	EC50	48h	Crustacea	6.5mg/l	1
	Endpoint	Test Duration (hr)	Species	Value	Source
	NOEC(ECx)	504h	Crustacea	1mg/l	2
(C10-16)alkyl D-	EC50	48h	Crustacea	7mg/l	2
alveonyranosido		96h	Fish	2.95mg/l	2
glycopyranoside	LC50	0011			

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

DO NOT discharge into sewer or waterways

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### Persistence and degradability

Ing	redient	Persistence: Water/Soil	Persistence: Air
glyc	cerol	LOW	LOW

### Bioaccumulative potential

Ingredient	Bioaccumulation
glycerol	LOW (LogKOW = -1.76)

# Mobility in soil

Ingredient	Mobility
glycerol	HIGH (Log KOC = 1)

#### **SECTION 13 Disposal considerations**

## Waste treatment methods

Product / Packaging disposal

- ▶ **DO NOT** allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- ► Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

# Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was a ppropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

Only dispose to the environment if a tolerable exposure limit has been set for the substance.

Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

# **SECTION 14 Transport information**

Labels Required		

Version No: 2.1

Page **16** of **19** 

VarioClean Eco 150 ml and 500 ml

Issue Date: **08/11/2024**Print Date: **13/11/2024** 

Marine Pollutant



HAZCHEM

Not Applicable

Version No: 2.1

VarioClean Eco 150 ml and 500 ml

Issue Date: **08/11/2024**Print Date: **13/11/2024** 

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

# 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
glycerol	Not Available
decyl-D-glucopyranoside	Not Available
cocamidopropylbetaine	Not Available
(C10-16)alkyl D- glycopyranoside	Not Available

#### 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
glycerol	Not Available
decyl-D-glucopyranoside	Not Available
cocamidopropylbetaine	Not Available
(C10-16)alkyl D- glycopyranoside	Not Available

# **SECTION 15 Regulatory information**

# Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002521	Animal Nutritional and Animal Care Products Group Standard 2020
HSR002530	Cleaning Products Subsidiary Hazard Group Standard 2020
HSR002535	Gases under Pressure Mixtures Subsidiary Hazard Group Standard 2020
HSR002503	Additives Process Chemicals and Raw Materials Subsidiary Hazard Group Standard 2020
HSR002606	Lubricants Lubricant Additives Coolants and Anti freeze Agents Subsidiary Hazard Group Standard 2020
HSR002612	Metal Industry Products Subsidiary Hazard Group Standard 2020
HSR002624	N.O.S. Subsidiary Hazard Group Standard 2020
HSR002638	Photographic Chemicals Subsidiary Hazard Group Standard 2020
HSR002644	Polymers Subsidiary Hazard Group Standard 2020
HSR002647	Reagent Kits Group Standard 2020
HSR002648	Refining Catalysts Group Standard 2020
HSR002653	Solvents Subsidiary Hazard Group Standard 2020
HSR002670	Surface Coatings and Colourants Subsidiary Hazard Group Standard 2020
HSR002684	Water Treatment Chemicals Subsidiary Hazard Group Standard 2020
HSR100425	Pharmaceutical Active Ingredients Group Standard 2020
HSR002600	Leather and Textile Products Subsidiary Hazard Group Standard 2020
HSR002544	Construction Products Subsidiary Hazard Group Standard 2020
HSR002549	Corrosion Inhibitors Subsidiary Hazard Group Standard 2020
HSR002552	Cosmetic Products Group Standard 2020
HSR002558	Dental Products Subsidiary Hazard Group Standard 2020
HSR002565	Embalming Products Subsidiary Hazard Group Standard 2020
HSR002571	Fertilisers Subsidiary Hazard Group Standard 2020
HSR002573	Fire Fighting Chemicals Group Standard 2021
HSR002578	Food Additives and Fragrance Materials Subsidiary Hazard Group Standard 2020
HSR002585	Fuel Additives Subsidiary Hazard Group Standard 2020
HSR002596	Laboratory Chemicals and Reagent Kits Group Standard 2020
HSR100580	Tattoo and Permanent Makeup Substances Group Standard 2020
HSR100757	Veterinary Medicines Limited Pack Size Finished Dose Group Standard 2020
HSR100758	Veterinary Medicines Non dispersive Closed System Application Group Standard 2020
HSR100759	Veterinary Medicines Non dispersive Open System Application Group Standard 2020
HSR100592	Agricultural Compounds Special Circumstances Group Standard 2020
HSR100756	Active Ingredients for Use in the Manufacture of Agricultural Compounds Group Standard 2020

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

Page **18** of **19** 

Part Number: Version No: **2.1** 

VarioClean Eco 150 ml and 500 ml

Issue Date: **08/11/2024**Print Date: **13/11/2024** 

#### glycerol is found on the following regulatory lists

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 4

Australian Inventory of Industrial Chemicals (AIIC)

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

#### decyl-D-glucopyranoside is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

#### cocamidopropylbetaine is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

Australian Inventory of Industrial Chemicals (AIIC)

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Land Transport Rule: Dangerous Goods 2005 - Schedule 1 Quantity limits for dangerous goods

#### (C10-16)alkyl D-glycopyranoside is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

New Zealand Inventory of Chemicals (NZIoC)

#### **Additional Regulatory Information**

Not Applicable

#### **Hazardous Substance Location**

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

#### **Certified Handler**

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

# Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

### **Tracking Requirements**

Not Applicable

### **National Inventory Status**

National Inventory	Status	
Australia - AIIC / Australia Non- Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (glycerol; decyl-D-glucopyranoside; cocamidopropylbetaine; (C10-16)alkyl D-glycopyranoside)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	No ((C10-16)alkyl D-glycopyranoside)	
Japan - ENCS	Yes	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'	
Taiwan - TCSI	Yes	
Mexico - INSQ	No (decyl-D-glucopyranoside; (C10-16)alkyl D-glycopyranoside)	
Vietnam - NCI	Yes	
Russia - FBEPH	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

# **SECTION 16 Other information**

Revision Date

08/11/2024

Chemwatch: 7918-44 Page 19 of 19

Version No: 2.1

#### VarioClean Eco 150 ml and 500 ml

Issue Date: 08/11/2024 Print Date: 13/11/2024

Initial Date

08/11/2024

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the BWES Classification committee using available literature references

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be

#### **Definitions and abbreviations**

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancer
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit。
  IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- ▶ BEI: Biological Exposure Index
- ▶ DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- ▶ MARPOL: International Convention for the Prevention of Pollution from Ships
- ▶ IMSBC: International Maritime Solid Bulk Cargoes Code
- IGC: International Gas Carrier Code
- ▶ IBC: International Bulk Chemical Code
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ▶ ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- ▶ PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- ► TCSI: Taiwan Chemical Substance Inventory
- ▶ INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- ▶ FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances